The Identification of Material Management Risk Factors Affecting The Time Performance in Fly Over Project Construction

Hafnidar A. Rani and Tamalkhani Syammaun

Civil Engineering Department, Faculty of Engineering Universitas Muhammadiyah Aceh Banda Aceh, Aceh, Indonesia hafnidar.ar@unmuha.ac.id, tamalkhani@unmuha.ac.id

Abstract

Material is everything and all requirement needed during the project construction to support the project activities so that the project can produce the goal achievement. Material management includes the planning and control related to the material viewed from various sectors including procurement, supply, purchase, delivery, acceptance, warehousing and distribution. One of the problems often faced is the material procurement delay. The material is not available when it is required and this condition causes the reduction of the workers' productivities. In addition, the workers' productivities reduction also affects the time performance of the project construction. The project manager needs to control the various activities in the project location. One of the importing factors is the time performance. This research aims to identify the most dominant factor in the material management affecting the time performance and to analyze the material management risk effect to the time performance in fly over project construction in Banda Aceh. The observation done to construction implementation teams (stakeholders) in Fly Over Project in Banda Aceh, they are the owner, supervision consultants and contractors. The statistical analysis used is validity test, reliability test, descriptive analysis and multiple linear regression. The most affecting material management risk factor to the time performance in the fly over project construction is quality control factor. It means that if quality control factor can be well handled, the time performance of the project construction will improve.

Keywords

Risk, Material management, Time performance

1. Introduction

In the construction project, there are various problem must be faced in the project completion (Pérez et al., 2010; Rani et al., 2013a; Qazi at al., 2016). One of the problems often faced is the material procurement delay (Marzouk and El-Rasas, 2014; Brahm and Tarziján, 2015; Aziz and Abdel-Hakam, 2016; Gebrehiwet and Luo, 2017). The material is not available when it is required and this condition causes the reduction of the workers' productivities (Ng et al., 2004; Abdel-Razak et al., 2007; Nasirzadeh and Nojedehi, 2013). The productivity reduction gives the contribution to cost swelling caused by the extension of workers' salary. In addition, the workers' productivities reduction also affects the time performance of the project construction (Brown et al., 2007; Lei et al., 2017, Rani et al. 2018). The project delay will be penalized or sanctioned by the owner to the contractor (Sambasivan and Soon, 2007; Doloi et al., 2012; Aziz, 2013; Senouci et al., 2016). The sanction is 1 per mile per day multiplied by the contract value. It will impact to the financial loss not only for small scale project but also for medium and large scale projects (Toor and Ogulana, 2008; Söderlund, 2010; Maier and Branzei, 2014; Lu et al., 2015; Patanakul et al., 2016; Liu et al., 2017).

The project runs well if the project can meet all requirements of the cost, time and quality (Atkinson, 1999; Khang and Myint, 1999; Gardiner and Stewart, 2000; Abdelsalam and Gad, 2009; Kim et al., 2012; Rani et al., 2013b; Rani, 2017). These three targets affect each other. The material procurement delay problem will cause the addition

of the time and the cost (Kaliba et al., 2009; Chan, 2001; Aliverdi et al.. 2013; Rani, 2015; Senouci et al., 2016; Sanchez et al., 2017). The most important is we realize that the knowledge and skill of good material management become important matter in running the project (Zhang et al., 2018). For example is how to establish the relationship and good communication to the vendor/supplier in order to avoid the material delivery delay (Aibinu and Jagboro, 2002; Müller and Turner, 2005; Mesa et al., 2016; Wu et al., 2017). Because the vendor often prefers giving the priority and delivering the material ordered in the many quantities (Mahmoud-Jouini et al., 2004). The good understanding of this risk factor will become knowledge base to establish effective and efficient material management system (Edwards and Browen, 1998; Ward, 1999; Mohanty and Deshmukh, 2001; Ibn-Homaid, 2002; Perera et al., 2009; Xia et al., 2018; Yang et al., 2018).

There are many studies conduct around the world to improve risk management in construction projects (del Caño and de la Cruz, 2002; Thevendran and Mawdesley, 2004; Wakshull, 2004; Pavlak, 2005; Luu et al., 2009; Green and Fontaine, 2016; Olechowski et al., 2016; Wang et al., 2016; Domingues et al., 2017; Muriana and Vizzini, 2017; Szymariski, 2017; Hernández, et al., 2018).

The development of Banda Aceh in the various sectors affects transportation problems such as the traffic jams in several roads. Simpang Surabaya is one of the intersections which has very high traffic density and one of the important points in Banda Aceh Road Network System because it serves the primary road network system. Therefore fly over construction becomes absolute that must be constructed to solve the traffic jam problem in the area (Rani et al., 2017). This bridge has been being constructed during 710 days since 21 December 2015 to 29 November 2017. This project is funded by the State Budged (APBN) which is IDR 250,124,483,000.00 (Two Hundred Fifty Billion One Hundred Twenty Four Million four Hundred Eighty Three Thousand Rupiah).

Related to the above background, the problem of this research is what the dominant risk factor in the material management affecting the time performance of the project construction is and how the effect of material management risk to the time performance in Simpang Surabaya Fly Over Project Construction in Banda Aceh. This research aims to identify the most dominant factor in the material management affecting the time performance and to analyze the material management risk effect to the time performance in Simpang Surabaya Fly over Project construction in Banda Aceh. The observation done to construction implementation teams (stakeholders) directly involved in the field of Simpang Surabaya Fly Over Project in Banda Aceh including the owner, supervision consultants and constructors. The independent variables used in this research are material management risk factors including planning and scheduling, contracting, coordination and core personnel, purchasing, delivering, quality control, storage and warehouse, field mobilization, consumption, supervision and controlling, budgeting, external factors, while the dependent variable is time performance. The statistical analysis used is validity test, reliability test, descriptive analysis and multiple linear regression using *Statistical Product and Service Solution* (SPSS). This research benefit is expected to be good knowledge for the researcher, and can be input to the contractor constructing Simpang Surabaya Fly over Project in Banda Aceh in handling material management.

2. Literature Review

2.1. **Risk**

Alijoyo (2006) stated that the risk can be defined from various view points. From the result of output view, it can be defined as the results or outputs which cannot be certainty predicted, dislike, and contra productive. While form the process view, it can be defined as the factors affecting the objective achievement and resulting undesirable consequences.

Fisk (1997) mentioned that the risk is the variation may occur naturally in any situation. No one can predict when the risk can occur. Therefore, the risk can also be interpreted as the probability of events occurring in the certain period.

2.2. Material Management

Asiyanto (2009) mentioned that the material is everything and all requirement needed during the project construction to support the project activities so that the project can produce the goal achievement. According to the process, the project materials can be divided into 4 categories as follows:

- 1. Raw materials are the materials delivered to the project location. They are still in the raw type for processing. The raw materials include stone, sand, cement, steel, and wood.
- 2. Finished materials are the material delivered to the project location and can be directly installed. The finished materials include tile, roof tile, glass, ceramic, and light.
- 3. Fixed materials are the material delivered to the project location as the fixed materials. They include ready mix concrete and hot mix asphalt.
- 4. Prefabricated materials are the materials casted or installed outside the project location by the other parties. When delivering to the project location, it is only installed. The prefabricated materials include precast concrete, steel frame, door and window sills.

Material management includes the planning and control related to the material viewed from various sectors including procurement, supply, purchase, delivery, acceptance, warehousing and distribution.

2.3. Material Management Risk Affecting the Time Performance

Andani (2011) mentioned that the material management risk affecting the time performance of the project is divided into some factors. The risk factors can be mentioned in Table 1.

Table 1. Material management risk factors affecting the time performance

Variable	Indicator	
Planning and scheduling	The difficulty in material procurement (imported material)	
	Material Specification which is less explicit/ less completed	
	The mistake in forecasting the field condition, weather, and future	
	condition	
	Mistake in planning the working scope	
	Less accurate and careful in material scheduling planning	
	Mistake in developing and applying the working method	
	Mistake in determining the transportation production capacity so that	
	the transportation tool available is not enough for material mobilization	
	Less planning for alternative material	
	Management planning for material transportation is less good	
	Lacking of knowledge about where and when the best material available	
Contracting	The sub clauses of the contract which are not completed	
	The misperception in understanding the clauses of the sub	
	contract/material specification	
	The weaknesses in solving the disagreement among involved parties	
	The Mistake in writing the contract clauses	
	The difference of the language used in the contract	
Coordination and core personnel	The communication/coordination system among the personnel which is	
	less effective	
	The procedure and bureaucracy systems which are complicated	
	The delay of decision making process	
	The mistake in delegating the task and authority	
	The project personnel located are less competence in the organization	
	structure	
Purchasing	The material scarcity of on the market which is not anticipated by the	
	contractor	
	The material source condition change to the project location	
	The change of policy and company rules in the research	
	Lest quality of the supplier	
	The materials are purchased using the traditional method (ordering	
	many at once but rarely needed)	
Delivering	The delay in material delivering to the location	
- · · · · · · · · · · · · · · · · · · ·	L	

	The change of material condition (broken/loss) during delivering	
	process	
	Accessibility during delivery process is less good	
Quality control	The material quality purchased does not match to the order	
7	The material quality does not match the specification	
Storage and warehouse	The material loss in the warehouse	
	The delay in storage system	
	The material is broken in the storage (due to the type of warehouse	
	which does not match the requirement)	
	The material storage is not grouped per material type	
	Less monitoring in the warehouse	
Field mobilization	Damage to material transportation during material distribution	
	The traffic management application does not run well	
	The congestion in the loading area	
Consumption	The material use wastefulness in the location	
	Frequent material transfer	
	Less understanding to the characteristic of the project location	
Supervision and controlling	Less coordination meeting in the field	
	Report system (recording) of the material flow is less good	
	Decision making system is less good	
	Less good inventories control of the material stocks	
Budgeting	Payment system selection is less appropriate	
	Payment media selection is less appropriate	
External	Economic condition change	
	Frequent change of the law regulations	
	The unpredictable conditions are often happened during the project	
	construction (natural disaster, politic, and others)	
G	The weather and climate conditions are less supported	

Source: Andani (2011)

2.4. Time Performance

Halpin (1998) mentioned that the project manager needs to control the various activities in the project location. One of the importing factors is the time performance. The time performance is the process comparing the field work and planned schedule. The project construction time criterias can be divided into 3 indicators such as slow, normal and fast durations.

3. Methodology

3.1. Data Collection

The data used in this research is primary and secondary data. The primary data is questionnaire. The data collection done is by distributing written document to the respondents to be answered. While the secondary data used is Aceh Province Map, Banda Aceh Map, Research Location Map, Rigid Pavement Layout, and Stakeholder Data obtained from PT. Jaya Konstruksi.

3.2. Population Determination

The population is stakeholder involved in Simpang Surabaya Fly over Project in Banda Aceh consisting of owner, supervision consultant, and contractor based on the data received from PT. Jaya Konstruksi on 2016. The stakeholder is 73 people. The total sampel from this research taken is total of the population.

3.3. Research Variable Determination

Very good (SB)

These research variables consist of independent variables (X) which are material management risk factors and dependent variable (Y) which are time performance.

3.4. Measurement Scale

The respondents' answers of the questionnaire use Likert Scale which every answer of the respondents can be explained in Table 2.

Performance No. **Answering Category** Score 1 Not Very Good (STB) Delay than the schedule > 2 weeks 1 2 Not Good (TB) Delay than the schedule between 1-2 weeks 2 3 Less Good (KB) Delay than the schedule < 1 week 3 On time or faster between 1-2 weeks Good (B) 4

Faster than the schedule > 2 weeks

Table 2. Answering category of related variable

4. Result

4

5

4.1. Validity Test

The result of validity test of every question has been processed and it can be explained in Table 3.

Variable	Factors	Statement	R_{count}	R_{table}
X1	Planning &	$X_{1.1} - X_{1.10}$	0.433 - 0.806	0.230
	scheduling			
X2	Contracting	$X_{2.1} - X_{2.5}$	0.580 - 0.737	0.230
X3	Coordination & core	$X_{3.1} - X_{3.5}$	0.715 - 0.875	0.230
	personnel			
X4	Purchasing	$X_{4.1} - X_{4.5}$	0.674 - 0.897	0.230
X5	Delivering	$X_{5.1} - X_{5.3}$	0.946 - 0.982	0.230
X6	Quality control	$X_{6.1} - X_{6.2}$	0.921 - 0.923	0.230
X7	Storage &	$X_{7.1} - X_{7.5}$	0.866 - 0.954	0.230
	warehouse			
X8	Field mobilization	$X_{8.1} - X_{8.3}$	0.910 - 0.949	0.230
X9	Consumption	$X_{9.1} - X_{9.3}$	0.637 - 0.862	0.230
X10	Supervision &	$X_{10.1} - X_{10.4}$	0.604 - 0.779	0.230
	controlling			
X11	Budgeting	$X_{11.1} - X_{11.2}$	0.854 - 0.885	0.230
X12	External	$X_{12.1} - X_{12.4}$	0.735 - 0.906	0.230

Table 3. Validity test

Table 3 shows that all statements given to the respondents has $R_{count} > R_{table}$. It means that all statements are valid.

4.2. Reliability Test

The result of reliability test for each variable has been processed and it can be explained in Table 4.

5

Table 4. Reliability test

Variable	Factors	Cronbach Alpha
X1	Planning & scheduling	0.866
X2	Contracting	0.734
X3	Coordination & core personnel	0.853
X4	Purchasing	0.870
X5	Delivering	0.963
X6	Quality control	0.824
X7	Storage & warehouse	0.936
X8	Field mobilization	0.916
X9	Consumption	0.672
X10	Supervision & controlling	0.684
X11	Budgeting	0.676
X12	External	0.842

The above table shows that all variables in the questionnaire has $Cronbach\ Alpha > 0.6$. It means based on the reliability test done to all variables results that all variables are reliable.

4.3. Descriptive Analysis

Descriptive analysis is used to detect the frequency of respondents' characteristic, frequency of questionnaire answer in problem solving. The problem is the most dominant risk factor of material management affecting the project time performance. It can be explained as below.

These respondents' characteristics are the stakeholders' characteristics consisting of owner, supervision consultants, contractors which are 73 respondents. The distribution of the respondents' characteristics can be shown in the column chart of 1 to 4.

The characteristic based on gender shows that almost all are males which are 70 respondents (95.89%). Only small part are females which are 3 respondents (4.11%). The respondents' distribution based on the gender can be shown in Figure 1.




Figure 1. Gender of respondents

The characteristic based on age shows that most respondent have 31-40 years old which are 39 respondents (53.42%). Almost half respondents have 20-30 years old which are 34 respondents (46.58%). The respondents' distribution based on the age can be shown in Figure 2.




Figure 2. Age of respondents

The characteristic based on the last education shows that most respondent have bachelor degree backgrounds which are 53 respondents (72.60%). Only small parts have diploma degree backgrounds which are14 respondents (19.18%) following by the senior high school backgrounds which are 6 respondents (8.22%). The respondents' distribution based on the last education can be shown in Figure 3.




Figure 3. Last education of respondents

The characteristic based on the stakeholder shows that most respondent are constructors which are 62 respondents (84.93%). Small parts are supervision consultants which are 7 respondents (9.59%) following by the owners which are 4 respondents (5.48%). The respondents' distribution based on the stakeholder can be shown in Figure 4.




Figure 4. Stakeholder of respondents

4.4. Material Dominant Risk Factor Affecting to the Time Performance in the Fly Over Project Construction

This analysis is intended to know perception of the owners, supervision consultants, and contractors about the most dominant of material management risk factors affecting the time performance in Banda Aceh Fly over Project Construction.

Based on Table 5, the indicator mean of each factor shows the interpretation of score percentage for each indicator. Most of stakeholders are very affected and the other are affected. It means that all material management risk indicators affect time performance in the fly over project.

Variable	Factors	Mean	Ratings
X1	Planning & scheduling	4.082	8
X2	Contracting	3.663	10
X3	Coordination & core personnel	3.592	12
X4	Purchasing	4.277	6
X5	Delivering	4.110	7
X6	Quality control	4.390	3
X7	Storage & warehouse	4.310	5
X8	Field mobilization	4.393	2
X9	Consumption	4.374	4
X10	Supervision & controlling	4.397	1

Table 5. Mean of material management risk factors affecting the time performance

Based on the table 5 above shows that the highest mean is obtained from the supervision and controlling factor which value is 4.397. It means that based on stakeholders' perceptions, the most dominant of material management risk factors affecting the time performance in fly over project construction is the supervision and controlling factor.

4.075

3.599

Budgeting

External

X11

X12

9

11

4.5. Multiple Linear Regression Analysis

Multiple linear regression analysis is used to determine the effect of material management risk factors to the time performance in fly over project construction in Banda Aceh by looking at the regression coefficient. The multiple regression coefficients that have been analyzed are summarized in Table 6.

Variable	Regression Coefficient	Significant
Constant	3.567	_
Planning & scheduling	0.002	0.000
Contracting	0.018	0.701
Coordination & core personnel	0.003	0.041
Purchasing	0.002	0.887
Delivering	0.002	0.740
Quality control	0.032	0.803
Storage & warehouse	0.001	0.029
Field mobilization	0.005	0.927
Consumption	0.002	0.721
Supervision & controlling	-0.016	0.851
Budgeting	0.020	0.240
External	-0.027	0.191

Table 6. Multiple linear regression coefficient

Based on the regression coefficient in Table 6, it is obtained the multiple linear regression analysis which can be shown in the below equations:

 $Y = 3.567 + 0.002X_{1} + 0.018X_{2} + 0.003X_{3} + 0.002X_{4} + 0.002X_{5} + 0.032X_{6} + 0.001X_{7} + 0.005X_{8} + 0.002X_{9} - 0.016X_{10} + 0.020X_{11} - 0.027X_{1.}$

The graph of multiple linear regression analysis which has been analyzed can be shown in Figure 5.




Figure 5. The graph of multiple linear regression

The graph shows that the points are located around the regression line. It means that the line represents all data taken so that the regression model can be accepted.

5. Discussion

In this research, there are 12 risk factors of material management affecting the time performance. From all the factors, it is obtained the most dominant risk factor of material management affecting time performance in the fly over project construction which is supervision and controlling factor.

Supervision and controlling factor is the part of management function which aims to effort the field implementation runs along with the schedule planned. Supervision and controlling factor consists of 4 indicators including less coordination meeting in the field, report system (recording) of the material flow is less good, and decision making system is less good, less good inventories control of the material stocks. The impact of material management risk from supervision and controlling factor is the work product and process become under control so that it affects the time performance of project construction. The action can be done to minimize or avoid the impact is by auditing the process and product; repairing the controlling system; creating the flow chart of the controlling completed with person in charge; and creating Standard Operating Procedures (SOP) and Job description.

Before the project activity starts, SOP and Job Description must be clear. SOP is a document relating to the procedure carried out chronologically to complete the work item in order to receive the most effective working product from the workers using the cheapest cost. Job description is the guide of the company to Personnel in performing the task for project controlling. These SOP and job descriptions are made by the company and project team, so that project authority and responsibility in the project controlling can adjust the implementation time.

The effect of the material management risk factors to the time performance in fly over project construction has been analyzed using multiple linear regression. This effect is the response between the action and the reaction. This means that when the risk factors of material management occur, the time performance in the flyover project will increase or decrease. Based on multiple linear regression coefficients analyzed, there are 10 risk factors of material management have positive affects and the rest of 2 factors have negative affects to the time performance in fly over project construction.

Positive effects imply that if one of material management the risk factors is well handled, the time performance of the fly over project will increase. The factors which have positive effects are quality control factor, budgeting factor, contracting factor, field mobilization factor, coordination and core personnel factor, planning and scheduling factor, purchasing factor, delivery factor, consumption factor and storage and warehouse factor. Negative effects imply that if one of material management the risk factor is well handled, the time performance of the fly over project will decrease. The factors which have negative effects are supervision and controlling factor and external factor.

Related to the above condition, the most dominant risk factor of material management affecting the time performance in the fly over project is quality control factor which have the highest regression coefficient as 0.032. It means that if quality control is well handled, the time performance in the project construction will increase. The handling can be done to the quality control is by reviewing the material in the plant before the material delivered, every material which does not meet the requirement must be returned, and the contract clause must clearly explain the material quantity, and the material used is based on the owner approval.

Acknowledgements

This research was supported by Universitas Muhammadiyah Aceh. We thank our colleagues from Universiti Malaysia Pahang who provided insight and expertise that assisted this research, although they may not agree with all of the interpretation and conclusion produced of this paper.

References

Abdelsalam, H. M. E. and Gad, M. M., Cost of quality in Dubai: An analytical case study of residential construction projects, *Int. J. Proj. Manag.*, vol. 27, no. 5, pp. 501–511, 2009.

Abdel-Razek, R., Abd Elshakour, M. H., and Abdel-Hamid, M., Labor productivity: Benchmarking and variability in Egyptian projects, *Int. J. Proj. Manag.*, vol. 25, no. 2, pp. 189–197, 2007.

- Aibinu, A. and Jagboro, G., The effects of construction delays on project delivery in Nigerian construction industry, *Int. J. Proj. Manag.*, vol. 20, no. 8, pp. 593-599, 2002.
- Alijoyo, A., Enterprise Risk Management, Ray Indonesia, Jakarta, 2016.
- Aliverdi, R., Naeni, L. M., and Salehipour, A., Monitoring project duration and cost in a construction project by applying statistical quality control charts, *Int. J. Proj. Manag.*, vol. 31, no. 3, pp. 411-423, 2013.
- Andani, S., Analisa resiko manajemen material dominan yang berpengaruh terhadap kinerja waktu pelaksanaan proyek gedung bertingkat BUMN, Universitas Indonesia, Depok, 2011.
- Asiyanto, Manajemen Resiko untuk Kontraktor, Pradnya Paramita, Jakarta, 2009.
- Atkinson, R., Project management: cost, time and quality, two best guesses and a phenomenon, its time to accept other success criteria, *Int. J. Proj. Manag.*, vol. 17, no. 6, pp. 337–342, 1999.
- Aziz, R., Ranking of delay factors in construction projects after Egyptian revolution, *Alexandria Eng. Journal*, vol. 52, no. 3, pp. 387-406, 2013.
- Aziz, R. F. and Abdel-Hakam, A. A., Exploring delay causes of road construction projects in Egypt, *Alexandria Eng. J.*, vol. 55, no. 2, pp. 1515–1539, 2016.
- Brahm, F. and Tarziján, J., Does complexity and prior interactions affect project procurement? Evidence from mining mega-projects, *Int. J. Proj. Manag.*, vol. 33, no. 8, pp. 1851–1862, 2015.
- Brown, A. W., Adams, J. D., and Amjad, A. A., The relationship between human capital and time performance in project management: A path analysis, *Int. J. Proj. Manag.*, vol. 25, no. 1, pp. 77–89, Jan. 2007.
- Chan, A., Time-cost relationship of public sector projects in Malaysia, *Int. J. Proj. Manag.*, vol. 19, no. 4, pp. 223–229, 2001.
- del Caño, A. and de la Cruz, M. P., Integrated methodology for project risk management, ... *Eng. Manag.*, vol. 128, no. December, pp. 473–486, 2002.
- Doloi, H., Sawhney, A., Iyer, K., and Rentala, S., Analysing factors affecting delays in India construction projects, *Int. J. Proj. Manag.*, vol. 30, no. 4, pp. 479–489, 2012.
- Domingues, M. S. Q., Baptista, A. L. F., and Diogo, M. T., Engineering complex systems applied to risk management in the mining industry, *Int. J. Min. Sci. Technol.*, vol. 27, no. 4, pp. 611–616, Jul. 2017.
- Edwards, P. J. and Bowen, P. A., Risk and risk management in construction: a review and future directions for research, *Journal of Engineering, Construction and Architectural Management*, vol. 5, no. 4, pp. 339-349, 1998.
- Fisk, E. R., Construction Project Administration, 5th Edition, New Jersey; Pretice Hall, New Jersey, 1997.
- Gardiner, P. and Stewart, K., Revisiting the golden triangle of cost, time and quality: the role of NPV in project control, success and failure, *Int. J. Proj. Manag.*, vol. 18, no. 4, pp. 251-256, 2000.
- Gebrehiwet, T. and Luo, H., Analysis of delay impact on construction project based on RII and correlation coefficient: Empirical study, *Procedia Eng.*, vol. 196, pp. 366–374, 2017.
- Green, P. and Fontaine, M., Project risk management, Enterprise Risk Manag., pp. 47-58, 2016.
- Halpin, D. W., Construction Management, John Wiley and Sons, USA, 1998.
- Hernández, M. L., Carreño, M. L., and Castillo, L., Methodologies and tools of risk management: Hurricane risk index (HRi), *Int. J. Disaster Risk Reduct.*, vol. 31, pp. 926–937, Oct. 2018.
- Ibn-Homaid, N. T., A comparative evaluation of construction and manufacturing materials management, *Int. J. Proj. Manag.*, vol. 20, no. 4, pp. 263–270, May 2002.
- Kaliba, C., Muya, M., and Mumba, K., Cost escalation and schedule delays in road construction projects in Zambia, *Int. J. Proj. Manag.*, vol. 27, no. 5, pp. 522–531, 2009.
- Khang, D. and Myint, Y., Time, cost and quality trade-off in project management: a case study, *Int. J. Proj. Manag.*, vol. 17, no. 4, pp. 249-256, 1999.
- Kim, J., Kang, C., and Hwang, I., A practical approach to project scheduling: considering the potential quality loss cost in the time-cost tradeoff problem, *Int. J. Proj. Manag.*, vol. 30, no. 2, pp. 264-272, 2012.
- Lei, Z., Tang, W., Duffield, C., Zhang, L., and Hui, F. K. P., The impact of technical standards on international project performance: Chinese contractors' experience, *Int. J. Proj. Manag.*, vol. 35, no. 8, pp. 1597–1607, Nov. 2017.
- Liu, J., Jin, F., Xie, Q., and Skitmore, M., Improving risk assessment in financial feasibility of international engineering projects: A risk driver perspective, *Int. J. Proj. Manag.*, vol. 35, no. 2, pp. 204-211, 2017.
- Lu, Y., Luo, L., Wang, H., Le, Y., and Shi, Q., Measurement model of project complexity for large-scale projects from task and organization perspective, *Int. J. Proj. Manag.*, vol. 33, no. 3, pp. 610-622, 2015.
- Luu, V. T., Kim, S. Y., Van Tuan, N., and Ogunlana, S. O., Quantifying schedule risk in construction projects using Bayesian belief networks, *Int. J. Proj. Manag.*, vol. 27, no. 1, pp. 39–50, 2009.

- Mahmoud-Jouini, S., Midler, C., and Garel, G., Time-to-market vs. time-to-delivery: Managing speed in engineering, procurement and construction projects, *Int. J. Proj. Manag.*, vol. 22, no. 5, pp. 359–367, 2004.
- Maier, E. and Branzei, O., On time and on budget: Harnessing creativity in large scale projects, *Int. J. Proj. Manag.*, vol. 32, no. 7, pp. 1123-1133, 2014.
- Marzouk, M. M. and El-Rasas, T. I., Analyzing delay causes in egyptian construction projects, *J. Adv. Res.*, vol. 5, no. 1, 2014.
- Mesa, H., Molenaar, K., and Alarcón, L., Exploring performance of the integrated project delivery process on complex building projects, *Int. J. Proj. Manag.*, vol. 34, no. 7, pp. 1089-1101, 2016.
- Mohanty, R. and Deshmukh, S., Reengineering of materials management system: A case study, *Int. J. Prod. Econ.*, vol. 70, no. 3, pp. 267–278, Apr. 2001.
- Müller, R. and Turner, J., The impact of principal-agent relationship and contract type on communication between project owner and manager, *Int. J. Proj. Manag.*, vol. 23, no. 5, pp. 398-403, 2005.
- Muriana, C. and Vizzini, G., Project risk management: A deterministic quantitative technique for assessment and mitigation, *Int. J. Proj. Manag.*, vol. 35, no. 3, pp. 320–340, 2017.
- Nasirzadeh, F. and Nojedehi, P., Dynamic modeling of labor productivity in construction projects, *Int. J. Proj. Manag.*, vol. 31, no. 6, pp. 903-911, 2013.
- Ng, S., Skitmore, R., Lam, K., and Poon, A., Demotivating factors influencing the productivity of civil engineering projects, *Int. J. Proj. Manag.*, vol. 22, no. 2, pp. 139–146, 2004.
- Olechowski, A., Oehmen, J., Seering, W., and Ben-Daya, M., The professionalization of risk management: What role can the ISO 31000 risk management principles play?, *Int. J. Proj. Manag.*, vol. 34, no. 8, pp. 1568–1578, Nov. 2016.
- Patanakul, P., Kwak, Y. H., Zwikael, O., and Liu, M., What impacts the performance of large-scale government projects?, *Int. J. Proj. Manag.*, vol. 34, no. 3, pp. 452–466, Apr. 2016.
- Pavlak, A., Project troubleshooting: Tiger teams for reactive risk management, *IEEE Eng. Manag. Rev.*, vol. 33, no. 1, pp. 36–48, 2005.
- Perera, B. A. K. S., Dhanasinghe and Rameezdeen, R., Risk management in road construction: The case of Sri Lanka. *International Journal of Strategic Property Management*, vol. 13, no. 2, pp. 87-102, 2009.
- Pérez, P. B., González-Cruz, M., and Pastor-Ferrando, J. P., Analysis of construction projects by means of value curves, *Int. J. Proj. Manag.*, 2010.
- Qazi, A., Quigley, J., Dickson, A., and Kirytopoulos, K., Project Complexity and Risk Management (ProCRiM): Towards modelling project complexity driven risk paths in construction projects, *Int. J. Proj. Manag.*, vol. 34, no. 7, pp. 1183–1198, Oct. 2016.
- Rani, H. A., Minimizing The Cost for Repairing Road with Pavement Recycling, *1st Jt. Conf. Indones.*, no. April, pp. 228 237, 2015.
- Rani, H. A., Optimization and Effectiveness of Bridge Construction Development Based on Value Engineering, *Int. J. Civil, Struct. Environ. Infrastruct. Eng. Res. Dev.*, vol. 7, no. 2, pp. 15–22, 2017.
- Rani, H. A., Abdullah, C. S., and Mohtar, S., Utilization on Project Management Function and Project Performance, *Malaysian Manag. J.*, vol. 17, pp. 77–113, 2013a.
- Rani, H. A., Abdullah, C. S., and Mohtar, S., A Study on Relationship between Project Management Function, Technology Utilization and Project Performance, *Int. J. Bussiness Technopreneursh.*, vol. 3, no. 1, pp. 51–74, 2013b.
- Rani, H. A., Amin, J., and Gunawan, The factors identification of the work safety and health (K3) program application in the fly over project construction in Banda Aceh, *Aceh Glob. Heal. Int. Conf.*, vol. 1, pp. 1–2, 2017.
- Rani, H. A., Isya, M., and Chalid, A., The Identification of The Most Dominant Contractor's Performance Factor Influencing The Road Preservation Quality Achievement using Long Segment, *Int. Conf. Sci. Eng. Technol.*, no. May, 2018.
- Sambasivan, M. and Soon, Y., Causes and effects of delays in Malaysian construction industry, *Int. J. Proj. Manag.*, vol. 25, no. 5, pp. 517–526, 2007.
- Sanchez, O. P., Terlizzi, M. A., and de O. C. de Moraes, H. R., Cost and time project management success factors for information systems development projects, *Int. J. Proj. Manag.*, vol. 35, no. 8, pp. 1608–1626, Nov. 2017.
- Senouci, A., Ismail, A., and Eldin, N., Time Delay and Cost Overrun in Qatari Public Construction Projects, *Procedia Eng.*, vol. 164, no. June, pp. 368–375, 2016.
- Söderlund, J., Knowledge entrainment and project management: The case of large-scale transformation projects, *Int. J. Proj. Manag.*, vol. 28, no. 2, pp. 130–141, 2010.
- Szymariski, P., Risk management in construction projects, *Procedia Eng.*, vol. 208, pp. 174–182, 2017.

Proceedings of the International Conference on Industrial Engineering and Operations Management Bangkok, Thailand, March 5-7, 2019

- Thevendran, V. and Mawdesley, M. J., Perception of human risk factors in construction projects: An exploratory study, *Int. J. Proj. Manag.*, vol. 22, no. 2, pp. 131–137, 2004.
- Toor, S. and Ogunlana, S., Critical COMs of success in large-scale construction projects: Evidence from Thailand construction industry, *Int. J. Proj. Manag.*, vol. 26, no. 4, pp. 420–430, 2008.
- Wang, C., Xu, B., Zhang, S., and Chen, Y, Influence of personality and risk propensity on risk perception of Chinese construction project managers, *Int. J. Proj. Manag.*, vol. 34, no. 7, pp. 1294–1304, 2016.
- Wakshull, M., Managing Risk in Organizations, Proj. Manag. J., vol. 35, no. 3, p. 65, 2004.
- Ward, S., Requirements for an Effective Project Risk Management Process, *Proj. Manag. J.*, vol. 30, no. 3, p. 37, 1999.
- Wu, G., Liu, C., Zhao, X., and Zuo, J., Investigating the relationship between communication-conflict interaction and project success among construction project teams, *Int. J. Proj. Manag.*, vol. 35, no. 8, pp. 1466-1482, 2017.
- Xia, N., Zou, P. X. W., Griffin, M. A., Wang, X., and Zhong, R., Towards integrating construction risk management and stakeholder management: A systematic literature review and future research agendas, *Int. J. Proj. Manag.*, vol. 36, no. 5, pp. 701–715, Jul. 2018.
- Yang, Q., Chin, K. S., and Li, Y. L., A quality function deployment-based framework for the risk management of hazardous material transportation process, *J. Loss Prev. Process Ind.*, vol. 52, pp. 81–92, Mar. 2018.
- Zhang, Y., Liu, S., Tan, J., Jiang, G., and Zhu, Q., Effects of risks on the performance of business process outsourcing projects: The moderating roles of knowledge management capabilities, *Int. J. Proj. Manag.*, vol. 36, no. 4, pp. 627–639, May 2018.

Biographies

Hafnidar A. Rani is an Associate Professor, and Dean of Engineering Faculty at the Muhammadiyah Aceh University, Indonesia. She graduated her Bachelor Degree from Syiah Kuala University as a Civil Engineer. Then she continued her Master Program in Management Magister of Syiah Kuala University. She commenced her doctoral program in Construction Project Management of Universiti Utara Malaysia. After receiving her bachelor degree, she became the Civil Engineering lecturer and teaching in Muhammadiyah Aceh University. Her subjects are Construction Management, Project Management, Research Methodology, Statistic and Probability, Value Engineering, and Construction Project Risk Management. She is actively conducting the researches especially in the last 6 years and also participating in seminar and conferences both national and international. She is also active as the keynote speaker in the seminar both national and international and as the reviewer of some Civil Engineering Journals. Her newest guideline book written is Construction Project Management produced in the beginning of 2016.